



Flexible Videoconferences That Meet Your Needs

Quick decision making and extensive information sharing are essential for today's business. Panasonic HD Visual Communication (HDVC*) System supports them with efficient communication in distance.

* HD Visual Communications System is abbreviated as HDVC hereafter.

HDVC Main Unit

HD Communication Camera, Boundary Microphone, HDMI cable sold separately.



KX-VC2000SX NEW
(To be released 4th quarter CY2016)
 • Full HD 1080p image quality
 • Expandable up to 24 sites connection with optional licence

KX-VC1600SX
 • Full HD 1080p image quality
 • Expandable up to 10 sites connection with optional licence

KX-VC1300SX
 • Full HD 1080p image quality

KX-VC1000SX NEW
(To be released 3rd quarter CY2016)
 • Full HD 1080p image quality
 • Point to point model

HDVC Mobile (HDVC Application)

(Windows/iOS/Android™)
 *iPhone and iPad supported



Optional Accessories*

*Sold separately

HD Communication Cameras



Boundary Microphones



(Due to product development, details are subject to change without notice.)

Up to 24 sites Multi-Point Connection

New HDVC have a Line-up covering point to point connection and up to 24 sites connection. It can be available for flexible system configuration to meet customers' needs.

Dual Network Connection for company internal and external network

HDVC is ready for connecting both internal and external network. No expensive equipment is required to connect external companies. (Dual Network is available on KX-VC2000SX/ KX-VC1600SX.)

Multi-Device stress-free conference

HDVC supports Multi-Device of Windows/iOS/Android™. The generation of packet losses for the HDVC System and HDVC Mobile is prevented by the rate control (AV-QoS), and lost packets are restored by the combined use of the forward error correction and automatic repeat request control.

Multi Monitor Capability

HDVC supports multi-monitors to show PC contents, and other party camera image. The KX-VC2000SX/ KX-VC1600SX supports Triple Monitors that enables even third monitor to show own site image. The KX-VC1300SX/ KX-VC1000SX* support Dual Monitors only.

* Option must be purchased.

Connecting with operating rooms

Real-time videoconferences can be held while viewing images of an ongoing operation on a monitor outside the operating room. This makes it possible to provide advanced treatment methods with some of the participating doctor in location other than the operating room.

3MOS 4K Ultra HD Camera
GP-UH532



Interoperability with other manufacturers videoconference units

HDVC supports conventional protocol of H.261/H.263/H.264 as well as H.239 dual stream of PC contents and camera image simultaneous display. This provides existing videoconference user step by step less expensive migration.

Specifications

Main Unit		KX-VC2000SX NEW	KX-VC1600SX	KX-VC1300SX	KX-VC1000SX NEW
Communication Method		SIP, H.323			
Video Compression Method		H.261 (mainstream only), H.263, H.263+, H.263++ (reception only), H.264 High Profile, H.264 Baseline Profile			
Audio Compression Method		G.711 μ -law, A-law [3.4 kHz@64 kbps] G.722 (7.0 kHz@64 kbps) G.722.1 (7.0 kHz@32 kbps) G.722.1 Annex C (14.0 kHz@48 kbps/24 kbps) MPEG-4 AAC-LD Mono (7.0 kHz@32 kbps, 14.0 kHz@64 kbps, 22.0 kHz@96 kbps) MPEG-4 AAC-LD Stereo (14.0 kHz@64 kbps, 22.0 kHz@96 kbps)			
No. of Channels		G.711/G.722/G.722.1/G.722.1 Annex C: 1 MPEG-4 AAC-LD Mono: 1/ MPEG-4 AAC-LD Stereo: 2			
Remote Camera Control		H.224, H.281 [Zoom/Pan/Tilt/Preset]			
Dual Stream	Method	H.239 (H.323), BFCP (SIP)			
	Multi-Monitor	3 displays		2 displays ^{*1}	
No. of Applicable Resolution Frames		Main: Max. 1080p 30 frames/second, Sub: Max. 1080p 30 frames/second			
Encryption		SRTP (AES 128 bit), H.235 (AES 128 bit)			
Other		H.460			
Communication Bandwidth		256 kbps to 18 Mbps			
Video	Compatible Resolutions ^{*2}	176 x 144p, 352 x 240p, 352 x 288p, 512 x 288p, 640 x 480p, 704 x 480p, 704 x 576p, 768 x 432p, 800 x 600p, 1024 x 768p, 1280 x 720p, 1280 x 768p, 1280 x 800p, 1920 x 1080p			
	No. of Frames	Max. 60 frames/second (When using H.264 1080p)			
	Screen Display	Full-screen, Picture in Picture, Picture with Picture, Side by Side			
Audio		Echo canceller, Auto gain control, Stationary noise reduction, Lip synch, Equalizer, Mic mute			
I/O Terminals	Video Input	Camera ^{*3}	HDMI main x 1, HDMI sub x 1 Input resolution: 1280 x 720p, 1920 x 1080i, 1920 x 1080p		
		PC	RGB x 1 (Mini D-sub 15pin), HDMI x 1 ^{*3} Input compatible resolution: VGA, SVGA, XGA, HD, WXGA, SXGA, FWXGA, WXGA+, WXGA++, UXGA, WSXGA+, Full-HD		
Video Output		HDMI x 2, HDMI x 1 (For own site/recording video) RCA x 1 (Component) Supported output resolutions: 1920 x 1080i, 1920 x 1080p	HDMI x 2 ^{*4} Supported output resolutions: 1920 x 1080i, 1920 x 1080p		
Audio Input		Digital Boundary Microphone x 1 (KX-VCA001X) Max. 4, Boundary Microphone x 1 (KX-VCA002X) Max. 1, HDMI, Stereo mini-plug ^{*5} x 1 (ϕ 3.5 mm) RCA, (Stereo) x 1		Boundary Microphone x 1 (KX-VCA002X) Max. 1, HDMI, Stereo mini-plug ^{*5} x 1 (ϕ 3.5 mm), RCA (Stereo) x 1	
Audio Output		HDMI ^{*6} , Stereo mini-plug ^{*5} x 1 (ϕ 3.5 mm), RCA x 1 (Stereo)			
Network		RJ45 x 2 1000BASE-T/100BASE-TX/10BASE-T Full Duplex	RJ45 x 1 1000BASE-T/100BASE-TX/10BASE-T Full Duplex		
External Control		RS-232C x 1 (Also used for maintenance)			
Others		USB 2.0 x 1, Camera Control Terminal x 1 (Not used)			
No. of Simultaneous Connection Sites		24 (Max.) / 16 (Default)	10 (Max.) / 6 (Default)	4 (Default)	Point to point
Content Sharing		PC (RGB/HDMI), Sub video camera (HDMI sub)			
USB Memory		Updating Software Import: Setting Address Book / Profile / Structural Data / Encryption Data / Start-up Screen / Delivery Tree List Export: Address Book / Profiles / Structural Data / Encryption Data / Delivery Tree List			
Network Protocol		TCP/IPv4, TCP/IPv6, UDP/IPv4, UDP/IPv6, DHCP, DNS, HTTP, HTTPS, TELNET, NTP			
Network Functions		Packet resending (ARQ), Forward Error Correction (FEC), Adaptive Rate Control (ARC), Reorder, Packet Shaping, Arbitrary Port Setting, NAT Compatibility, Encryption, IP Precedence/DiffServ Support			
External Control		Control via web browser/HTTP CGI, TELNET, RS-232C			
Connection Modes		IP mode, NAT Traversal Service, IP/NAT Traversal Service			
Dimensions [width x depth x height] [Unit: mm] *Excluding projecting parts		T.B.D.		Approx. 320 x 230 x 61	
Weight		T.B.D.		Approx. 2.0 kg	
Power Input		T.B.D.		AC 100-240 V, -1.4A, 50/60 Hz	
Power Consumption		T.B.D.		Max.: approx. 45 W, Standby: 0.6 W	Max.: approx. 37 W, Standby: 0.6 W
DC Power Input		T.B.D.		DC 24 V, 2.5 A	
Operating Temperature		T.B.D.		0 °C to 40 °C	
Operating Humidity		T.B.D.		10 % to 90 % (Non-condensing)	

* When connected to an other brand device or other brand MCU (Multi-point Control Unit), connection conditions vary depending on the specifications of the other brand device or other brand MCU.

*1 KX-VC1000SX is necessary an optional license to use.*2 Varies due to the settings of the HDVC System and the network condition. *3 HDCP is not supported. *4 KX-VC1000SX is necessary an optional license to use HDMI2. *5 Dedicated 3-pole stereo mini-plug. *6 Audio cannot be output simultaneously to HDMI1/HDMI2.

• Specifications and design are subject to change without notice. • All monitor screens are simulated. • Windows is a registered trademark of Microsoft Corporation in the United States and other countries. • Android™ is a trademark or registered trademark of Google Inc. • iPhone and iPad are trademarks of Apple Inc. • iOS is an operating system name of Apple Inc. • iOS is a trademark or registered trademark of Cisco Systems, Inc. or other related company in the United States and other countries. • HDMI, the HDMI logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC.

DISTRIBUTED BY :

Panasonic

HD Visual Communications System:
<http://panasonic.net/psn/products/hdvc/>

MG-HDCL029EN